


# For Pneumatic and Electric Power Bits (Type A)

Shape	Model No.	Size Tip×Overall Length (ℓ)	Heat treatment classification	Inner Ctn.	Outer Ctn.	Applicable models
						<b>VESSEL</b> GT-H4R-H4PR-H4.5-H5R-H5P-PH4-PH5-S4.5D-S4.5DR- PLP-PLZ-PLP-PLH-36MLR-36HS-36.5D-P4.5D- P4.5DR-P4.5S-P6.5D-P6.5DR-P6.5S-P6HS-P6HS- P6.5D-S4TR-S4TS-S4TG-S5TR-S5TB-S5TG-S5TS
6.35mm	<b>M-A16</b> 	⊕ 2X4.5X65	H	10	100	<b>NPK</b> SD-4 ND-5LPI-6LFIY-6HSY-6HPAY-6SDY-6FDY NPW-450A-DYO-550A-DYO-450E-DYO-450A-TDY- 550A-TDY <b>Fuji Kuki</b> FPW-330SD-10-440D-20-550D-20-660D-30-770D-20- 400SD-10-440SD-10-550SD-10-660SD-10 FET-440-20-550D-20-660-20 FW-55XD-70-80-65XD-60-5PX-60-6PX-60- 6PMD-10-44SD-10-66SD-10-44PD-10-66PD-10- 44SAD-10-66SAD-10-44PAD-10-66PAD-10 FPT-440D-10-10L-550D-10-10L-660D-10-10L- 440SD-10-550SD-10-660SD-10
		100	H	10	100	
		150	H	10	100	
	<b>D81</b>	⊕ 2X 82	X.H.E	10	100	<b>MAX</b> AT-4D-750P <b>Yutani</b> D-6SSAL-5WPEA-6SPAL-6SPALE-600SHA- 6WSHPFA-602A-6SHPAL DH-4.5PEA <b>Yokota</b> YL-70B-80B YX-180SB-280SB-380SB-500SB-80B-180B-280B- 380B-500B YD-400SB-4.5PBZK-6SPBZ-6SPBZ- 600PBZ-650PBZ-40PBZ-4.5LBZ-6WBZK-600SBZ- 670B-670BF-670BR-670BRF Y-40SB-41B-46B <b>Toshiba</b> CJEL-144VA <b>Hitachi Koki</b> WH-6DC-8DYA-9DM-9DM2-10AC-10VA2- 12DM-12DMR-12DM2-12VB-12AB-12DK-12VA- 12VC-12VD-14DM-14VA-14DH WF-10A-12DM <b>Makita</b> TP-124D, 123D, 130D, 150D, 1000D, 061D 6919D, 6930D, 6960D, 6919N, 6954, 6954SP, 6954SPK, 6904V, 6700N, AD603, FS230D <b>Matsushita</b> EZ-7200-6507-7201-6506-6502-6605- 6582-6404-6120-6780-7301-7270-7202-7203 EZT141-640-607-610-611-612 <b>Ryobi</b> ID-8-12-80-121-130-140, CID-800, BID-1211-900-1220-1255-1230-1211-122-123, MID-10 <b>Tonichi</b> AUF5N
6.35mm						
	<b>A20</b>	A/F 4.5X55	O.D. φ7.5	10	250	<b>Yokota</b> YL-70B-80B YX-180SB-280SB-380SB-500SB-80B-180B-280B- 380B-500B YD-400SB-4.5PBZK-6SPBZ-6SPBZ- 600PBZ-650PBZ-40PBZ-4.5LBZ-6WBZK-600SBZ- 670B-670BF-670BR-670BRF Y-40SB-41B-46B <b>Toshiba</b> CJEL-144VA <b>Hitachi Koki</b> WH-6DC-8DYA-9DM-9DM2-10AC-10VA2- 12DM-12DMR-12DM2-12VB-12AB-12DK-12VA- 12VC-12VD-14DM-14VA-14DH WF-10A-12DM <b>Makita</b> TP-124D, 123D, 130D, 150D, 1000D, 061D 6919D, 6930D, 6960D, 6919N, 6954, 6954SP, 6954SPK, 6904V, 6700N, AD603, FS230D <b>Matsushita</b> EZ-7200-6507-7201-6506-6502-6605- 6582-6404-6120-6780-7301-7270-7202-7203 EZT141-640-607-610-611-612 <b>Ryobi</b> ID-8-12-80-121-130-140, CID-800, BID-1211-900-1220-1255-1230-1211-122-123, MID-10 <b>Tonichi</b> AUF5N
		5 X 55	8.5	10	250	
		5.5X55	10	10	250	
		100	10	10	250	
		6 X 55	10	10	200	
		100	10	10	200	
		7 X 55	13	10	200	
		100	13	10	150	
		8 X 55	13	10	200	
		100	13	10	150	
		9 X 55	16	10	150	
		9.6X55	16	10	150	
		10 X 55	16	10	150	
		100	16	10	100	
		12 X 55	19	10	100	
		100	19	10	100	
		13 X 55	19	10	100	
	100	19	10	50		
	14 X 55	20	10	100		
	15 X 55	22	10	50		
	17 X 55	23	10	50		
	12X65X100	18	10	100		
	13X65X100	19	10	100		
	A/F 7X50	13	10	200		
	10X50	16	10	150		
6.35mm	<b>MA20S</b> Side magnet	A/F 5/16" (8mm) X 55	13	10	100	 The magnet holds the bolt and nut.
		A/F 3/8" (9.6mm) X 55	16	10	100	
		A/F 10mm X 55	16	10	100	

● For the order, specify the Model No., size, heat treatment class and quantity.  
Ex.) A16 ⊕ 6X45G 100 pcs.

■ Connection of a bit and a power tool  
The size of a bit clamping part is determined in consideration of the installed condition of each power tool.



TYPE 6.35mm ●  
M-A16, D81, A20, A20-3,  
A20-5, MA20S