

For Pneumatic and Electric Power Bits (Type B)



Shape	Model No.	Size Tip×Overall Length (ℓ)	Heat treatment classification	Inner Ctn.	Outer Ctn.	Applicable models
H6.35mm						
6.35mm ● 	B43	⊕ 1× 75	X.H	10	100	Uryu UX-U-UW-ALPHA-UBP-UL-ULT Screwdrivers, US-350W-45W-450WB-5W-50W-6W- 350PW-450PW-5PW-6PW- 652PW-50-5PB-5 US-LT60P-LT31PB-LT41PB-LT51PB-LT20B- LT30B-17-LT30B-11-LT40B-21- LT40B-15-LT50B-LT30BL-LT40BL- LT30B-LT40B-LT10B NPK ND-5LPX-6LFAX-6HPAX-6HSX NPD-50-50S-60-60S-60T-80-80S-80T NPW-450A-DXO-550A-DXO-450EA-DXO- 450A-TDX-550A-TDX Fuji Kuki FPW-330SD-1-440D-2-550D-2-660D-3- 770D-2-400SD-1-440SD-1-550SD-1- 660SD-1 FET-44D-2-55D-2-66D-2 FW-44SD-1-66SD-1-44PAD-1-66PAD-1- 44PD-1-66PD-1-44PAD-1-66PAD-1- 5SX-7-5SX-8-6SX-6-6PX-6- 6PLD-1-6PX-6-6PHD-1-6PMD-1-FD-4- 5-4P-5P-4PH-1 FPT-44D-1-1L-55D-1-1L-66D-1-1L- 440SD-1-550SD-1-660SD-1 Yutani DH-6PL-6PLE-45PEB D-500SHB-6SPBLE-6WSHPE-8WPE- 5WPE-6SSBEL-602B-6WSHSB DH-4.5SB-6SEL-6SELB Yokota TKa70A-YL70A-80A Y-41A-46A YX-180SA-280SA-380SA-500SA-180A- 280A-280CA-380A-500A-80A-500CA YEX-150A-501A-150SA-300SA-500SA- 100SA-120A-120SA YD-400SCA-500SCA-5PHCA-3A-4A- 5A-6WAZK-6SPZ-6SPTZ-650PZ- 40PZ-4.5PZK-600PZ-4.5SZ-4.5LAZ- 600SZ-670A-670AF-670AR-670AR-F Y-40SA Atlas-Copco LUM series- LUF series-TWIST series- EU series-ETB series-COMBI series- EP series Following Tool models are applicable only for the single end bits. Hios CL-9000, VZ-4504-4506 Delvo DLV- 8150-1141-1161-1171-7251- 8251-8152-7252-8252 Kanon N6-N12-N20-N30-N50-N100STDK N6-N12-N20-N30-N50-N100LTDK N10-N20-N50DPSK N10-N20-N50DPSKI 9K-150P Tonichi U60CN-100CN, ULR120CN-ULR250CN, UR500CN, M660CN-250CN, MF6N-MF12N, LTD15CN-1000CN, RTD15CN-500CN, BMLD15CN-30CN, BMRD15CN-30CN, NTD15CN-1000CN, RNTD15CN-500CN, FTD50CN-400CN, FTD2CN-S-400CN2-S, STC50CN-STC400CN, RTD2260CN, 500CN
		⊕ 2× 50	X.H.E	10	100	
		75	X.H.G.E	10	100	
		100	X.H.G.E	10	100	
		150	X.H.G.	10	100	
200	G	10	100			
⊕ 3× 75	H.E	10	100			
100	H.E	10	100			
6.35mm ● TAPPING BIT (B43H) <p>These are the special tapping bits for M4 - M5 tapping crews. It is suitable for the works where a large torque is given to the tip.</p>	B43H	⊕ 2× 75	H	10	100	
		100	H	10	100	
		150	H	10	100	
6.35mm ● TORSION BIT <p>Patented</p>	BT43	⊕ 2×3.5×75	H	10	100	
		100	H	10	100	
		100	H	10	100	
H6.35mm						
6.35mm ● 	B35	⊕ 1× 50	X.H	10	100	
		75	X.H	10	100	
		⊕ 1×4.5×100	H	10	100	
		⊕ 2× 50	X.G	10	100	
		75	X.H.G.E	10	100	
		100	H.G.E	10	100	
		150	X.H.G.E	10	100	
		⊕ 2×4.5×100	H	10	100	
		⊕ 3× 75	X.H.E	10	100	
		100	X.H.E	10	100	
		150	G	10	100	
		⊖ 6× 75	E	10	100	
		A/F 2× 75	H	10	100	
		100	H	10	100	
		2.5× 75	H	10	100	
100	H	10	100			
3× 75	H	10	100			
100	H	10	100			
4× 75	H	10	100			
100	H	10	100			
5× 75	G	10	100			
100	G	10	100			
6× 75	G	10	100			
100	G	10	100			
6.35mm ● 	B39	⊕ 2× 40	H	10	100	
		100	H	10	100	
6.35mm ● 	B45	A/F 5.5×75	O.D. φ 10	10	250	
		100	10	10	250	
		6×100	10	10	200	
		7× 75	13	10	200	
		100	13	10	150	
		8× 75	13	10	200	
		100	13	10	150	
		150	13	10	100	
		10× 75	16	10	150	
		100	16	10	100	
		150	16	10	100	
		12×100	18	10	100	
13× 75	19	10	100			
100	19	10	100			
14×100	20	10	100			

●For the order, specify the Model No., size, heat treatment class and quantity. Ex.) B43 ⊕2×50H pcs.

